

DCE-S 10/12 Plus

COMPACT INSTANTANEOUS WATER HEATER

PRODUCT-NO.: 238154

Enjoy reliable heat Life has its ups and downs. So we think it's reassuring to have a hot water supply in your home that you can always count on. With this compact instantaneous water heater, water at a pleasant temperature is a given. With efficiency that is second to none.

Very easy to operate With its minimal dimensions yet powerful output, this appliance supplies either several hand washbasins or a shower with water at your preferred temperature. Thanks to the rotary selector, it's easy to make adjustments. The end result is reliable hot water as an integral part of your day.



DCE-S 6/8 Plus

Product-No.: 238153

The main features

Compact instantaneous water heater with electronic closed-loop control

Very good energy efficiency thanks to 3i technology

Accurate temperature settings from 20 °C to 60 °C

Temperature limit can be fixed at 43 °C, 50 °C or 55 °C

Suitable for showers

Exceptionally slimline, compact design



Type	DCE-S 6/8 Plus	DCE-S 10/12 Plus
Part no.	238153	238154

Technical data

Rated voltage	220 V	220 V
Rated voltage 1	220 V	220 V
Rated voltage 2	230 V	230 V
Rated voltage 3	240 V	240 V
Rated output	6.0/8.0 kW	10.0/12.0 kW
Rated output 1	6.0/8.0 kW	10.0/12.0 kW
Rated output 2	6.6/8.7 kW	11.0/13.1 kW
Rated output 3	7.2/9.6 kW	12.0/14.3 kW
Rated current	27.3/36.4 A	45.5/54.5 A
Rated current 1	27.3/36.4 A	45.5/54.5 A
Rated current 2	28.5/38.0 A	47.8/57.0 A
Rated current 3	30.0/40.0 A	50.0/59.5 A
Fuse protection	30/40 A	50/60 A
Fuse protection 1	30/40 A	50/60 A
Fuse protection 2	30/40 A	50/60 A
Fuse protection 3	30/40 A	50/60 A
Frequency	50/60 Hz	50/60 Hz
Frequency 1	50/60 Hz	50/60 Hz
Frequency 2	50/60 Hz	50/60 Hz
Frequency 3	50/60 Hz	50/60 Hz
Phases	1/N/PE	1/N/PE

Conductivity $\sigma_{15} \leq$	910 $\mu S/cm$	910 $\mu S/cm$
Resistivity $\rho_{15} \geq$	1100 $\Omega\ cm$	1100 $\Omega\ cm$
IP rating	IP25	IP25
Temperature setting	20-60 $^{\circ}C$	20-60 $^{\circ}C$
Colour	white	white
Switch-on water flow rate	1.3 l/min	1.3 l/min
Height	372 mm	372 mm
Width	217 mm	217 mm
Depth	109 mm	109 mm
Weight	2.50 kg	2.50 kg
Energy efficiency class	A	A

Contact information

Do you have additional questions? Then please do not hesitate to contact us, we would be only too happy to help:

Call 0151 436 96

Or send an e-mail to

sales@stiebel-eltron.ie

Only a qualified contractor should carry out the installation, commissioning, maintenance and repair of this appliance. Where applicable and prior to installation the electricity and/or water utility companies should be notified of your intention to install the product.