

FCR 28/180 E

ACCESSORIES

PRODUCT-NO.: 000695

The main features

Replaceable copper heating element

For matching to individual usage scenarios

High hot water convenience thanks to powerful heating elements

Variable temperature setting via rotary selector



FCR 21/60

Product-No.: 071330



FCR 21/120 E

Product-No.: 071331



FCR 28/120 E

Product-No.: 000694



Type	FCR 21/60	FCR 21/120 E	FCR 28/120 E
Part no.	071330	071331	000694

Technical data

Connected load ~ 400 V	2-6 kW	8/12 kW	12 kW
Power supply	1/N/PE, 3/N/PE	1/N/PE, 2/N/PE, 3/PE	3/PE
Rated voltage	230/400 V	230/400 V	400 V
Coil voltage	230 V	230 V	400 V
Frequency	50/60 Hz	50/60 Hz	50 Hz
Version	Dual/single circuit	Single circuit	Single circuit
Integral contactor	X	-	X
IP rating	IP24	IP24	IP24
Immersion depth	400 mm	400 mm	325 mm
Flange diameter	210 mm	210 mm	280 mm



Type	FCR 28/180 E
Part no.	000695

Technical data

Connected load ~ 400 V	18 kW
Power supply	3/PE
Rated voltage	400 V
Coil voltage	400 V
Frequency	50 Hz
Version	Single circuit
Integral contactor	X
IP rating	IP24
Immersion depth	325 mm
Flange diameter	280 mm

Contact information

Do you have additional questions? Then please do not hesitate to contact us, we would be only too happy to help:

Call 0151 436 96

Or send an e-mail to

sales@stiebel-eltron.ie

Only a qualified contractor should carry out the installation, commissioning, maintenance and repair of this appliance. Where applicable and prior to installation the electricity and/or water utility companies should be notified of your intention to install the product.