

BHE 175 T Plus

BATHROOM RADIATOR

PRODUCT-NO.: 238715

Heat your bathroom the convenient way

These electric bathroom radiators supply you efficiently with the right amount of heat, just where you need it, all year round. Their blend of appealing design and functionality is a real winner. The operating controls are fitted at the perfect height for you to be able to adjust the temperature with ease.

Multiple uses of heat

Thanks to the slender round pipes and evenly distributed heat, you can hang your hand and bath towels on the radiator at several levels to dry or warm up. With their particular properties, the bathroom radiators in this series are ideal for use as heat generators or interim heaters in spring/autumn.

The main features

Electric-only operation due to factory filling with heat transfer medium

Can also be connected to the hot water heating network

Premium design with round pipes

Operating controls with illuminated LCD screen

With variable temperature adjustment

Version with integral rapid heater



BHE 50 Plus

Product-No.: 239141



BHE 75 Plus

Product-No.: 238713



BHE 100 Plus

Product-No.: 238714



| Type | BHE 50 Plus | BHE 75 Plus | BHE 100 Plus |
|----------|-------------|-------------|--------------|
| Part no. | 239141 | 238713 | 238714 |

Technical data

| | | | |
|------------------------------------------|----------------------------|----------------------------|----------------------------|
| Power supply | 1/N ~ 230 V | 1/N ~ 230 V | 1/N ~ 230 V |
| Rated voltage | 230 V | 230 V | 230 V |
| Rated current | 2.2 A | 3.3 A | 4.4 A |
| Rated output | 500 W | 750 W | 1000 W |
| Connected load | 500 W | 750 W | 1000 W |
| Heating output to EN 442 (75/65 - 20 °C) | 367 W | 571 W | 876 W |
| Heating output F/R - T (70/55 - 24 °C) | 125 W | 194 W | 298 W |
| Setting range | 10-28 °C | 10-28 °C | 10-28 °C |
| Number of ribs | 20 | 30 | 37 |
| IP rating | IP24 | IP24 | IP24 |
| Protection class | II | II | II |
| Colour | traffic white, RAL 9016 | traffic white, RAL 9016 | traffic white, RAL 9016 |
| Height | 1090 mm | 1590 mm | 1830 mm |
| Width | 500 mm | 500 mm | 550 mm |
| Depth | 117 mm | 117 mm | 117 mm |
| Weight | 12.00 kg | 19.00 kg | 23.00 kg |



| | |
|----------|----------------|
| Type | BHE 175 T Plus |
| Part no. | 238715 |

Technical data

| | |
|------------------------------------------|----------------------------|
| Power supply | 1/N ~ 230 V |
| Rated voltage | 230 V |
| Rated current | 7.6 A |
| Rated output | 1750 W |
| Connected load | 1750 W |
| Heating output to EN 442 (75/65 - 20 °C) | 571 W |
| Heating output F/R - T (70/55 - 24 °C) | 194 W |
| Setting range | 10-28 °C |
| Number of ribs | 30 |
| IP rating | IP24 |
| Protection class | II |
| Colour | traffic white, RAL 9016 |
| Height | 1590 mm |
| Width | 500 mm |
| Depth | 130 mm |
| Weight | 20.00 kg |

Depth including wall mounting bracket

Contact information

Do you have additional questions? Then please do not hesitate to contact us, we would be only too happy to help:

Call 0151 436 96

Or send an e-mail to

sales@stiebel-eltron.ie

Only a qualified contractor should carry out the installation, commissioning, maintenance and repair of this appliance. Where applicable and prior to installation the electricity and/or water utility companies should be notified of your intention to install the product.