


BHE 75 Plus

BATHROOM RADIATOR

PRODUCT-NO.: 238713

These electric bathroom radiators supply you efficiently with the right amount of heat, just where you need it, all year round. Their blend of appealing design and functionality is a real winner. The operating controls are fitted at the perfect height for you to be able to adjust the temperature with ease.



Thanks to the slender round pipes and evenly distributed heat, you can hang your hand and bath towels on the radiator at several levels to dry or warm up. With their particular properties, the bathroom radiators in this series are ideal for use as heat generators or interim heaters in spring/autumn.

The main features


Electric-only operation due to factory filling with heat transfer medium

Can also be connected to the hot water heating network

Premium design with round pipes

Operating controls with illuminated LCD screen

With variable temperature adjustment



Type	BHE 50 Plus	BHE 75 Plus	BHE 100 Plus
Part no.	239141	238713	238714

Heating output

Rated heating output P _{nom}	0.50 kW	0.75 kW	1.00 kW
Minimum heating output (standard value) P _{min}	0.00 kW	0.00 kW	0.00 kW
Maximum continuous heating output P _{max,c}	0.50 kW	0.75 kW	1.00 kW

Auxiliary power consumption

H rated heating output e _{lmax}	0.00 kW	0.00 kW	0.00 kW
H minimum heating output e _{lmin}	0.00 kW	0.00 kW	0.00 kW
Dby mode e _{lSB}	0.00 kW	0.00 kW	0.00 kW

Type of heating output/room temperature control

Single stage heating output, no room temperature control	-	-	-
Two or more manual stages, no room temperature control	-	-	-
With mechanic thermostat room temperature control	-	-	-
With electronic room temperature control	-	-	-
Electronic room temperature control plus day timer	-	-	-
Electronic room temperature control plus week timer	x	x	x

Other control options

Room temperature control, with presence detection	-	-	-
Room temperature control, with open window detection	-	-	-
With distance control option	-	-	-
With adaptive start control	x	x	x
With working time limitation	-	-	-
With black bulb sensor	-	-	-



Type	BHE 175 T Plus
Part no.	238715

Heating output

Rated heating output P _{nom}	1.75 kW
Minimum heating output (standard value) P _{min}	0.00 kW
Maximum continuous heating output P _{max,c}	1.75 kW

Auxiliary power consumption

H rated heating output e _{Hmax}	0.00 kW
H minimum heating output e _{Hmin}	0.00 kW
Dby mode e _{SB}	0.00 kW

Type of heating output/room temperature control

Single stage heating output, no room temperature control	-
Two or more manual stages, no room temperature control	-
With mechanic thermostat room temperature control	-
With electronic room temperature control	-
Electronic room temperature control plus day timer	-
Electronic room temperature control plus week timer	x

Other control options

Room temperature control, with presence detection	-
Room temperature control, with open window detection	-
With distance control option	-
With adaptive start control	x
With working time limitation	-
With black bulb sensor	-

Depth including wall mounting bracket

Contact information

Do you have additional questions? Then please do not hesitate to contact us, we would be only too happy to help:

Call 0151 436 96

Or send an e-mail to

sales@stiebel-eltron.ie

Only a qualified contractor should carry out the installation, commissioning, maintenance and repair of this appliance. Where applicable and prior to installation the electricity and/or water utility companies should be notified of your intention to install the product.