


CND 200

CONVECTORS

PRODUCT-NO.: 234816

With this product, the warmth reaches you in more ways than one. Since two heating systems are integrated in this direct heating appliance, it not only radiates cosy warmth, but also convects it via the indoor air. As a result, you enjoy a pleasant and comfortable room temperature. The appliance's elegant design ensures that it blends in perfectly with your living environment.



Easily set your preferred temperature on the appliance and benefit from greater savings: the wall mounted duo convector automatically lowers the temperature when you leave the room. If you open the windows to let fresh air in, the heater switches off automatically.

The main features

Wall mounted duo convector – ideal as an auxiliary heater or interim heater in spring/autumn

Even, pleasant room air heating

Modern and high grade design

Operating controls with illuminated LCD screen

Weekly timer, frost protection and open window detection

Electronic control unit with presence detection

ON/OFF switch and overheating protection

Permanent connection with FIL control core



Type	CND 75	CND 100	CND 150
Part no.	234813	234814	234815

Heating output

Rated heating output P _{nom}	0.80 kW	1.00 kW	1.50 kW
Minimum heating output (standard value) P _{min}	0.00 kW	0.00 kW	0.00 kW
Maximum continuous heating output P _{max,c}	0.80 kW	1.00 kW	1.50 kW

Auxiliary power consumption


H rated heating output e _{lmax}	0.00 kW	0.00 kW	0.00 kW
H minimum heating output e _{lmin}	0.00 kW	0.00 kW	0.00 kW
Dby mode e _{lSB}	0.00 kW	0.00 kW	0.00 kW

Type of heating output/room temperature control

Single stage heating output, no room temperature control	-	-	-
Two or more manual stages, no room temperature control	-	-	-
With mechanic thermostat room temperature control	-	-	-
With electronic room temperature control	-	-	-
Electronic room temperature control plus day timer	-	-	-
Electronic room temperature control plus week timer	x	x	x

Other control options

Room temperature control, with presence detection	x	x	x
Room temperature control, with open window detection	x	x	x
With distance control option	-	-	-
With adaptive start control	-	-	-
With working time limitation	-	-	-
With black bulb sensor	-	-	-



Type	CND 200
Part no.	234816

Heating output

Rated heating output P _{nom}	2.00 kW
Minimum heating output (standard value) P _{min}	0.00 kW
Maximum continuous heating output P _{max,c}	2.00 kW

Auxiliary power consumption

H rated heating output e _{lmax}	0.00 kW
H minimum heating output e _{lmin}	0.00 kW
Dby mode e _{lSB}	0.00 kW

Type of heating output/room temperature control

Single stage heating output, no room temperature control	-
Two or more manual stages, no room temperature control	-
With mechanic thermostat room temperature control	-
With electronic room temperature control	-
Electronic room temperature control plus day timer	-
Electronic room temperature control plus week timer	x

Other control options

Room temperature control, with presence detection	x
Room temperature control, with open window detection	x
With distance control option	-
With adaptive start control	-
With working time limitation	-
With black bulb sensor	-

Depth including wall mounting bracket

Contact information

Do you have additional questions? Then please do not hesitate to contact us, we would be only too happy to help:

Call 0151 436 96

Or send an e-mail to

sales@stiebel-eltron.ie

Only a qualified contractor should carry out the installation, commissioning, maintenance and repair of this appliance. Where applicable and prior to installation the electricity and/or water utility companies should be notified of your intention to install the product.