

# CNS 150 Connect UK

CONVECTORS

PRODUCT-NO.: 205642

Use an intuitive app to control your home heating and gain full transparency of energy consumption and costs through user-friendly statistics. Whether you just don't want to get up off the sofa or you are flying home from across the world, you can login to the app to set your heating just how you want it.



## The main features

Suitable for up to 10 rooms with up to 4 heaters each

---

Individual time programmes for each room with 2 or more heaters

---

Option to use external room temperature sensors for even more comfort in larger rooms where 2 or more units are installed

---

Installation wizard for initial setup

---

Metal casing and slimline design

---

Weekly timer, frost protection and open window detection for maximum operating efficiencies

---

Unit learns when to turn on to have your room at your target temperatures right at the start of your programmed times



Type	CNS 50 Connect UK	CNS 75 Connect UK	CNS 100 Connect UK
Part no.	205639	205640	205641

## Heating output

Rated heating output P <sub>nom</sub>	0.50 kW	0.75 kW	1.00 kW
Minimum heating output (standard value) P <sub>min</sub>	0.00 kW	0.00 kW	0.00 kW
Maximum continuous heating output P <sub>max,c</sub>	0.50 kW	0.75 kW	1.00 kW

## Auxiliary power consumption

H rated heating output e <sub>Hmax</sub>	0.00 kW	0.00 kW	0.00 kW
H minimum heating output e <sub>Hmin</sub>	0.00 kW	0.00 kW	0.00 kW
Dby mode e <sub>SB</sub>	0.00 kW	0.00 kW	0.00 kW

## Type of heating output/room temperature control

Single stage heating output, no room temperature control	-	-	-
Two or more manual stages, no room temperature control	-	-	-
With mechanic thermostat room temperature control	-	-	-
With electronic room temperature control	-	-	-
Electronic room temperature control plus day timer	-	-	-
Electronic room temperature control plus week timer	x	x	x

## Other control options

Room temperature control, with presence detection	-	-	-
Room temperature control, with open window detection	x	x	x
With distance control option	x	x	x
With adaptive start control	x	x	x
With working time limitation	-	-	-
With black bulb sensor	-	-	-



Type	CNS 150 Connect UK	CNS 200 Connect UK	CNS 250 Connect UK
Part no.	205642	205643	205644

## Heating output

Rated heating output P <sub>nom</sub>	1.50 kW	2.00 kW	2.50 kW
Minimum heating output (standard value) P <sub>min</sub>	0.00 kW	0.00 kW	0.00 kW
Maximum continuous heating output P <sub>max,c</sub>	1.50 kW	2.00 kW	2.50 kW

## Auxiliary power consumption

H rated heating output e <sub>lmax</sub>	0.00 kW	0.00 kW	0.00 kW
H minimum heating output e <sub>lmin</sub>	0.00 kW	0.00 kW	0.00 kW
Dby mode e <sub>lSB</sub>	0.00 kW	0.00 kW	0.00 kW

## Type of heating output/room temperature control

Single stage heating output, no room temperature control	-	-	-
Two or more manual stages, no room temperature control	-	-	-
With mechanic thermostat room temperature control	-	-	-
With electronic room temperature control	-	-	-
Electronic room temperature control plus day timer	-	-	-
Electronic room temperature control plus week timer	x	x	x

## Other control options

Room temperature control, with presence detection	-	-	-
Room temperature control, with open window detection	x	x	x
With distance control option	x	x	x
With adaptive start control	x	x	x
With working time limitation	-	-	-
With black bulb sensor	-	-	-



Type	<b>CNS 300 Connect UK</b>
Part no.	205645

### Heating output

Rated heating output P <sub>nom</sub>	3.00 kW
Minimum heating output (standard value) P <sub>min</sub>	0.00 kW
Maximum continuous heating output P <sub>max,c</sub>	3.00 kW

### Auxiliary power consumption

H rated heating output e <sub>Hmax</sub>	0.00 kW
H minimum heating output e <sub>Hmin</sub>	0.00 kW
Dby mode e <sub>LSB</sub>	0.00 kW

### Type of heating output/room temperature control

Single stage heating output, no room temperature control	-
Two or more manual stages, no room temperature control	-
With mechanic thermostat room temperature control	-
With electronic room temperature control	-
Electronic room temperature control plus day timer	-
Electronic room temperature control plus week timer	x

### Other control options

Room temperature control, with presence detection	-
Room temperature control, with open window detection	x
With distance control option	x
With adaptive start control	x
With working time limitation	-
With black bulb sensor	-

Depth including wall mounting bracket

**Contact information**

Do you have additional questions? Then please do not hesitate to contact us, we would be only too happy to help:

Call 0151 436 96

Or send an e-mail to

[sales@stiebel-eltron.ie](mailto:sales@stiebel-eltron.ie)

Only a qualified contractor should carry out the installation, commissioning, maintenance and repair of this appliance. Where applicable and prior to installation the electricity and/or water utility companies should be notified of your intention to install the product.