

# CNS-U 1000 Plus LCD (UK)

CONVECTORS

PRODUCT-NO.: 205869

**High on heat, low on space.**

Sometimes there's just not much room – even for a heater. That is why this wall mounted convector is very slimline. With a minimal depth, it nevertheless delivers outstanding thermal comfort.

**Enjoy a wide range of benefits.** The convector blends into its surroundings perfectly, efficiently delivering cosy warmth. The comfort functions of the integral controller, such as the weekly timer and open window detection, highlight the efficiency and high quality features of the appliance.

**The main features**

---

Permanent connection with FIL control core

---

Control unit with self-learning capability: automatic calculation of the preheat time in timer mode

---

Metal casing and slimline design

---

Even, quiet, air heating

---

Operating controls with illuminated LCD screen

---

ON/OFF switch and overheating protection

---

Wall mounted convector – ideal as a supplementary heater or interim heater in spring/autumn

---

Weekly timer, frost protection and open window detection

**CNS-U 500 Plus LCD (UK)**

Product-No.: 205867

**CNS-U 750 Plus LCD (UK)**

Product-No.: 205868

**CNS-U 1500 Plus LCD (UK)**

Product-No.: 205870

**CNS-U 2000 Plus LCD (UK)**

Product-No.: 205871

**CNS-U 2500 Plus LCD (UK)**

Product-No.: 205872

**CNS-U 3000 Plus LCD (UK)**

Product-No.: 205873



Type	CNS-U 500 Plus LCD (UK)	CNS-U 750 Plus LCD (UK)	CNS-U 1000 Plus LCD (UK)
Part no.	205867	205868	205869

## Technical data

Power supply	1/N/PE ~240 V	1/N/PE ~240 V	1/N/PE ~240 V
Rated voltage	240 V	240 V	240 V
Rated current	2,1 A	3,1 A	4,2 A
Connected load	0,5 kW	0,75 kW	1,0 kW
IP rating	IP24	IP24	IP24
Protection class	I	I	I
Colour	signal white, RAL 9003	signal white, RAL 9003	signal white, RAL 9003
Setting range	5-30 °C	5-30 °C	5-30 °C
Height	450 mm	450 mm	450 mm
Width	348 mm	426 mm	426 mm
Depth	100 mm	100 mm	100 mm
Weight	4.00 kg	4.60 kg	4.60 kg



Type	CNS-U 1500 Plus LCD (UK)	CNS-U 2000 Plus LCD (UK)	CNS-U 2500 Plus LCD (UK)
Part no.	205870	205871	205872

## Technical data

Power supply	1/N/PE ~240 V	1/N/PE ~240 V	1/N/PE ~240 V
Rated voltage	240 V	240 V	240 V
Rated current	6,3 A	8,3 A	10,4 A
Connected load	1,5 kW	2,0 kW	2,5 kW
IP rating	IP24	IP24	IP24
Protection class	I	I	I
Colour	signal white, RAL 9003	signal white, RAL 9003	signal white, RAL 9003
Setting range	5-30 °C	5-30 °C	5-30 °C
Height	450 mm	450 mm	450 mm
Width	582 mm	738 mm	894 mm
Depth	100 mm	100 mm	100 mm
Weight	6.00 kg	7.70 kg	9.20 kg



Type	CNS-U 3000 Plus LCD (UK)
Part no.	205873

### Technical data

Power supply	1/N/PE ~240 V
Rated voltage	240 V
Rated current	12,5 A
Connected load	3 kW
IP rating	IP24
Protection class	I
Colour	signal white, RAL 9003
Setting range	5-30 °C
Height	450 mm
Width	1050 mm
Depth	100 mm
Weight	10.90 kg

Depth including wall mounting bracket

## **Contact information**

Do you have additional questions? Then please do not hesitate to contact us, we would be only too happy to help:

Call 0151 436 96

Or send an e-mail to

[sales@stiebel-eltron.ie](mailto:sales@stiebel-eltron.ie)

Only a qualified contractor should carry out the installation, commissioning, maintenance and repair of this appliance. Where applicable and prior to installation the electricity and/or water utility companies should be notified of your intention to install the product.