

# CNS-U 2500 Plus LCD (UK)

CONVECTORS

PRODUCT-NO.: 205872

Sometimes there's just not much room – even for a heater. That is why this wall mounted convector is very slimline. With a minimal depth, it nevertheless delivers outstanding thermal comfort.

The convector blends into its surroundings perfectly, efficiently delivering cosy warmth. The comfort functions of the integral controller, such as the weekly timer and open window detection, highlight the efficiency and high quality features of the appliance.



## The main features

Permanent connection with FIL control core

---

Control unit with self-learning capability: automatic calculation of the preheat time in timer mode

---

Metal casing and slimline design

---

Even, quiet, air heating

---

Operating controls with illuminated LCD screen

---

ON/OFF switch and overheating protection

---

Wall mounted convector – ideal as a supplementary heater or interim heater in spring/autumn

---

Weekly timer, frost protection and open window detection



Type	CNS-U 500 Plus LCD (UK)	CNS-U 750 Plus LCD (UK)	CNS-U 1000 Plus LCD (UK)
Part no.	205867	205868	205869

## Heating output

Rated heating output P <sub>nom</sub>	0.50 kW	0.75 kW	1.00 kW
Minimum heating output (standard value) P <sub>min</sub>	0.00 kW	0.00 kW	0.00 kW
Maximum continuous heating output P <sub>max,c</sub>	0.50 kW	0.75 kW	1.00 kW

## Auxiliary power consumption

H rated heating output e <sub>Hmax</sub>	0.00 kW	0.00 kW	0.00 kW
H minimum heating output e <sub>Hmin</sub>	0.00 kW	0.00 kW	0.00 kW
Dby mode e <sub>LSB</sub>	0.00 kW	0.00 kW	0.00 kW

## Type of heating output/room temperature control

Single stage heating output, no room temperature control	-	-	-
Two or more manual stages, no room temperature control	-	-	-
With mechanic thermostat room temperature control	-	-	-
With electronic room temperature control	-	-	-
Electronic room temperature control plus day timer	-	-	-
Electronic room temperature control plus week timer	x	x	x

## Other control options

Room temperature control, with presence detection	-	-	-
Room temperature control, with open window detection	x	x	x
With distance control option	-	-	-
With adaptive start control	x	x	x
With working time limitation	-	-	-
With black bulb sensor	-	-	-



Type	CNS-U 1500 Plus LCD (UK)	CNS-U 2000 Plus LCD (UK)	CNS-U 2500 Plus LCD (UK)
Part no.	205870	205871	205872

## Heating output

Rated heating output P <sub>nom</sub>	1.50 kW	2.00 kW	2.50 kW
Minimum heating output (standard value) P <sub>min</sub>	0.00 kW	0.00 kW	0.00 kW
Maximum continuous heating output P <sub>max,c</sub>	1.50 kW	2.00 kW	2.50 kW

## Auxiliary power consumption

H rated heating output e <sub>Hmax</sub>	0.00 kW	0.00 kW	0.00 kW
H minimum heating output e <sub>Hmin</sub>	0.00 kW	0.00 kW	0.00 kW
Dby mode e <sub>LSB</sub>	0.00 kW	0.00 kW	0.00 kW

## Type of heating output/room temperature control

Single stage heating output, no room temperature control	-	-	-
Two or more manual stages, no room temperature control	-	-	-
With mechanic thermostat room temperature control	-	-	-
With electronic room temperature control	-	-	-
Electronic room temperature control plus day timer	-	-	-
Electronic room temperature control plus week timer	x	x	x

## Other control options

Room temperature control, with presence detection	-	-	-
Room temperature control, with open window detection	x	x	x
With distance control option	-	-	-
With adaptive start control	x	x	x
With working time limitation	-	-	-
With black bulb sensor	-	-	-



Type	<b>CNS-U 3000 Plus LCD (UK)</b>
Part no.	205873

#### Heating output

Rated heating output P <sub>nom</sub>	3.00 kW
Minimum heating output (standard value) P <sub>min</sub>	0.00 kW
Maximum continuous heating output P <sub>max,c</sub>	3.00 kW

#### Auxiliary power consumption

H rated heating output e <sub>Hmax</sub>	0.00 kW
H minimum heating output e <sub>Hmin</sub>	0.00 kW
Dby mode e <sub>ISB</sub>	0.00 kW

#### Type of heating output/room temperature control

Single stage heating output, no room temperature control	-
Two or more manual stages, no room temperature control	-
With mechanic thermostat room temperature control	-
With electronic room temperature control	-
Electronic room temperature control plus day timer	-
Electronic room temperature control plus week timer	x

#### Other control options

Room temperature control, with presence detection	-
Room temperature control, with open window detection	x
With distance control option	-
With adaptive start control	x
With working time limitation	-
With black bulb sensor	-

Depth including wall mounting bracket

**Contact information**

Do you have additional questions? Then please do not hesitate to contact us, we would be only too happy to help:

Call 0151 436 96

Or send an e-mail to

[sales@stiebel-eltron.ie](mailto:sales@stiebel-eltron.ie)

Only a qualified contractor should carry out the installation, commissioning, maintenance and repair of this appliance. Where applicable and prior to installation the electricity and/or water utility companies should be notified of your intention to install the product.