

SHS 2400

STORAGE HEATING

PRODUCT-NO.: 200183

This storage heater integrates extremely well into your living environment. It has such a slimline design that it is eminently suitable for wall mounting. However, the appliance's elegant appearance means it is just as impressive when installed as a floorstanding heater.



This storage heater's features are also impressive. Clever functions ensure temperatures that are optimally tailored to your needs. They also enable economical operation. You can enjoy pleasant warmth without worrying.

The main features

Slimline wall mounted or floorstanding storage heater

Intelligent automatic charging with C-Plus Technology for convenient, energy efficient operation

Integral room temperature controller with weekly timer and open window detection

Easily accessible operating controls with illuminated LCD screen

Long service life

Extremely quiet operation due to low noise crossflow fan



Type	SHS 1200	SHS 1800	SHS 2400
Part no.	200181	200182	200183

Wärmeleistung

Rated heating output P _{nom}	0.60 kW	0.90 kW	1.20 kW
Minimum heating output (standard value) P _{min}	0.00 kW	0.00 kW	0.00 kW
Maximum continuous heating output P _{max,c}	1.00 kW	1.50 kW	1.80 kW

Hilfsstromverbrauch

Auxiliary power consumption with rated heating output el _{max}	0.00 kW	0.00 kW	0.00 kW
Auxiliary power consumption with minimum heating output el _{min}	0.00 kW	0.00 kW	0.00 kW
Auxiliary power consumption in standby mode el _{SB}	0.00 kW	0.00 kW	0.00 kW

Art der Wärmeleistung/Raumtemperaturkontrolle

Type of heating output/room temperature control: Single stage heating output, no room temperature control	-	-	-
Type of heating output/room temperature control: Two or more manually adjustable stages, no room temperature control	-	-	-
Type of heating output/room temperature control: Room temperature control with mechanical thermostat	-	-	-
Type of heating output/room temperature control: With electronic room temperature control	-	-	-
Type of heating output/room temperature control: Electronic room temperature control and time of day control	-	-	-
Type of heating output/room temperature control: Electronic room temperature control and day of week control	x	x	x

Sonstige Regelungsoptionen

Other control options: Room temperature control with presence detection	-	-	-
Other control options: Room temperature control with window open detection	x	x	x
Other control options: With remote control option	-	-	-
Other control options: With adaptive control of heating startup	x	x	x
Other control options: With operating time limitation	-	-	-
Other control options: With black bulb sensor	-	-	-



Type	SHS 3000	SHS 3600	SHS 4200
Part no.	200184	200185	200186

Wärmeleistung

Rated heating output P _{nom}	1.50 kW	1.80 kW	2.10 kW
Minimum heating output (standard value) P _{min}	0.00 kW	0.00 kW	0.00 kW
Maximum continuous heating output P _{max,c}	2.20 kW	2.60 kW	2.80 kW

Hilfsstromverbrauch

Auxiliary power consumption with rated heating output el _{max}	0.00 kW	0.00 kW	0.00 kW
Auxiliary power consumption with minimum heating output el _{min}	0.00 kW	0.00 kW	0.00 kW
Auxiliary power consumption in standby mode el _{SB}	0.00 kW	0.00 kW	0.00 kW

Art der Wärmeleistung/Raumtemperaturkontrolle

Type of heating output/room temperature control: Single stage heating output, no room temperature control	-	-	-
Type of heating output/room temperature control: Two or more manually adjustable stages, no room temperature control	-	-	-
Type of heating output/room temperature control: Room temperature control with mechanical thermostat	-	-	-
Type of heating output/room temperature control: With electronic room temperature control	-	-	-
Type of heating output/room temperature control: Electronic room temperature control and time of day control	-	-	-
Type of heating output/room temperature control: Electronic room temperature control and day of week control	x	x	x

Sonstige Regelungsoptionen

Other control options: Room temperature control with presence detection	-	-	-
Other control options: Room temperature control with window open detection	x	x	x
Other control options: With remote control option	-	-	-
Other control options: With adaptive control of heating startup	x	x	x
Other control options: With operating time limitation	-	-	-
Other control options: With black bulb sensor	-	-	-



Type	SHS 4800
Part no.	200187

Wärmeleistung

Rated heating output P _{nom}	2.40 kW
Minimum heating output (standard value) P _{min}	0.00 kW
Maximum continuous heating output P _{max,c}	3.70 kW

Hilfsstromverbrauch

Auxiliary power consumption with rated heating output e _{lmax}	0.00 kW
Auxiliary power consumption with minimum heating output e _{lmin}	0.00 kW
Auxiliary power consumption in standby mode e _{lSB}	0.00 kW

Art der Wärmeleistung/Raumtemperaturkontrolle

Type of heating output/room temperature control: Single stage heating output, no room temperature control	-
Type of heating output/room temperature control: Two or more manually adjustable stages, no room temperature control	-
Type of heating output/room temperature control: Room temperature control with mechanical thermostat	-
Type of heating output/room temperature control: With electronic room temperature control	-
Type of heating output/room temperature control: Electronic room temperature control and time of day control	-
Type of heating output/room temperature control: Electronic room temperature control and day of week control	x

Sonstige Regelungsoptionen

Other control options: Room temperature control with presence detection	-
Other control options: Room temperature control with window open detection	x
Other control options: With remote control option	-
Other control options: With adaptive control of heating startup	x
Other control options: With operating time limitation	-
Other control options: With black bulb sensor	-

Overall depth = 21 mm with wall clearance mesh

Contact information

Do you have additional questions? Then please do not hesitate to contact us, we would be only too happy to help:

Call 0151 436 96

Or send an e-mail to

sales@stiebel-eltron.ie

Only a qualified contractor should carry out the installation, commissioning, maintenance and repair of this appliance. Where applicable and prior to installation the electricity and/or water utility companies should be notified of your intention to install the product.