

HUK 100 Set

ACCESSORIES

PRODUCT-NO.: 203711

The main features

Set with two changeover dampers

Robust design for a long service life

Available for various dimensions



HUK 125 Set

Product-No.: 203712



HUK 150 Set

Product-No.: 203713



HUK 200 Set

Product-No.: 203714



| | | | |
|----------|-------------|-------------|-------------|
| Type | HUK 100 Set | HUK 125 Set | HUK 150 Set |
| Part no. | 203711 | 203712 | 203713 |

Technical data

| | | | |
|------------------------|------------------------------------|------------------------------------|------------------------------------|
| Connection | DN 100 | DN 125 | DN 150 |
| kVS value | 150 m ³ /h | 260 m ³ /h | 400 m ³ /h |
| Leakage rate | tight, leakage rate A (EN 12266-1) | tight, leakage rate A (EN 12266-1) | tight, leakage rate A (EN 12266-1) |
| Runtime | 150 s / 90° | 150 s / 90° | 35 s / 90° |
| IP rating | IP54 | IP54 | IP66 |
| Control | Open/closed | Open/closed | Open/closed |
| Butterfly valve weight | 4 kg | 6.7 kg | 7.4 kg |
| Rotary drive weight | 4.1 kg | 4.1 kg | 5.8 kg |



| | |
|----------|-------------|
| Type | HUK 200 Set |
| Part no. | 203714 |

Technical data

| | |
|------------------------|------------------------------------|
| Connection | DN 200 |
| kVS value | 820 m ³ /h |
| Leakage rate | tight, leakage rate A (EN 12266-1) |
| Runtime | 35 s / 90° |
| IP rating | IP66 |
| Control | Open/closed |
| Butterfly valve weight | 14 kg |
| Rotary drive weight | 5.8 kg |

Availability on request

Contact information

Do you have additional questions? Then please do not hesitate to contact us, we would be only too happy to help:

Call 0151 436 96

Or send an e-mail to

sales@stiebel-eltron.ie

Only a qualified contractor should carry out the installation, commissioning, maintenance and repair of this appliance. Where applicable and prior to installation the electricity and/or water utility companies should be notified of your intention to install the product.