

UP 25/7.5 PCV

ACCESSORIES

PRODUCT-NO.: 201620

The main features

Electronically controlled circulation pump with variable differential control

Energy efficiency index (EEL): 0.20

Can be controlled via either a PWM signal or differential pressure

Delivery head max. 10 m

**UP 25/1-8 PCV**

Product-No.: 205285

**UP 30/1-8 PCV**

Product-No.: 205286

**UP 40/1-8 E**

Product-No.: 206633

**UP 50/1-12 E**

Product-No.: 206636



Type	UP 25/1-8 PCV	UP 25/7.5 PCV	UP 30/1-8 PCV
Part no.	205285	201620	205286

Technical data

Energy Efficiency Index EEI	0.20	0.20	0.20
Connection	G 1 1/2	G 1 1/2	G 2
Delivery head	8.00 m	8.40 m	8.00 m
Max. flow rate	9.50 m³/h	4.00 m³/h	9.00 m³/h
Power consumption	200 W	10-60 W	130 W
Rated voltage	230 V	230 V	230 V
Control via 0-10 V signal with IF module	x	-	x
Control via differential pressure	x	x	x
Control via PWM signal	x	x	x
Installation length (centre distance)	180 mm	180 mm	180 mm



Type	UP 40/1-8 E	UP 50/1-12 E
Part no.	206633	206636

Technical data

Energy Efficiency Index EEI	0.23	0.23
Connection	DN 40	DN 50
Delivery head	8.00 m	12.00 m
Max. flow rate	15.00 m³/h	29.00 m³/h
Power consumption	12-310 W	25-590 W
Rated voltage	230 V	230 V
Control via 0-10 V signal with IF module	x	x
Control via differential pressure	x	x
Control via PWM signal	-	-
Installation length (centre distance)	220 mm	280 mm

Contact information

Do you have additional questions? Then please do not hesitate to contact us, we would be only too happy to help:

Call 0151 436 96

Or send an e-mail to

sales@stiebel-eltron.ie

Only a qualified contractor should carry out the installation, commissioning, maintenance and repair of this appliance. Where applicable and prior to installation the electricity and/or water utility companies should be notified of your intention to install the product.