

## UPF 30/1-8 E

### ACCESSORIES

Energy efficient brine circuit pump (EEI  $\leq 0.23$ ), electronically controlled, with vapour diffusion-proof thermal insulation.

#### The main features

Reliable and energy efficient brine circulation pump

---

Electronic closed-loop control

---

Insulation shell included in delivery

---

with connecting cable and non-return valve

PRODUCT-NO.: 232532



**UPF 40/1-8 E**

Product-No.: 227413



**UPF 50/1-12 E**

Product-No.: 227414



Type	UPF 30/1-8 E	UPF 40/1-8 E	UPF 50/1-12 E
Part no.	232532	227413	227414

## Technical data

Energy Efficiency Index EEI	0.23	0.23	0.23
Connection	G 2	DN 40	DN 50
Delivery head	8.00 m	8.00 m	12.00 m
Max. flow rate	8.00 m <sup>3</sup> /h	15.00 m <sup>3</sup> /h	29.00 m <sup>3</sup> /h
Power consumption	8-130 W	12-310 W	25-590 W
Rated voltage	230 V	230 V	230 V
Control via 0-10 V signal with IF module	-	-	-
Control via differential pressure	x	x	x
Control via PWM signal	-	-	-
Installation length (centre distance)	180 mm	220 mm	280 mm

## **Contact information**

Do you have additional questions? Then please do not hesitate to contact us, we would be only too happy to help:

Call 0151 436 96

Or send an e-mail to

[sales@stiebel-eltron.ie](mailto:sales@stiebel-eltron.ie)

Only a qualified contractor should carry out the installation, commissioning, maintenance and repair of this appliance. Where applicable and prior to installation the electricity and/or water utility companies should be notified of your intention to install the product.