

UPF 50/1-12 E

ACCESSORIES

PRODUCT-NO.: 227414

Energy efficient brine circuit pump ($EEL \leq 0.23$), electronically controlled, with vapour diffusion-proof thermal insulation.

The main features

Reliable and energy efficient brine circulation pump

Electronic closed-loop control

Insulation shell included in delivery

**UPF 30/1-8 E**

Product-No.: 232532

**UPF 40/1-8 E**

Product-No.: 227413



Type	UPF 30/1-8 E	UPF 40/1-8 E	UPF 50/1-12 E
Part no.	232532	227413	227414

Technical data

Energy Efficiency Index EEI	0.23	0.23	0.23
Connection	G 2	DN 40	DN 50
Delivery head	8.00 m	8.00 m	12.00 m
Max. flow rate	8.00 m³/h	15.00 m³/h	29.00 m³/h
Power consumption	8-130 W	12-310 W	25-590 W
Rated voltage	230 V	230 V	230 V
Control via 0-10 V signal with IF module	-	-	-
Control via differential pressure	x	x	x
Control via PWM signal	-	-	-
Installation length (centre distance)	180 mm	220 mm	280 mm

Contact information

Do you have additional questions? Then please do not hesitate to contact us, we would be only too happy to help:

Call 0151 436 96

Or send an e-mail to

sales@stiebel-eltron.ie

Only a qualified contractor should carry out the installation, commissioning, maintenance and repair of this appliance. Where applicable and prior to installation the electricity and/or water utility companies should be notified of your intention to install the product.