

WPL Plus Pack 1

AIR SOURCE HEAT PUMPS

PRODUCT-NO.: 204911

The main features

Air source heat pump set for maximum efficiency in new build or modernisation

Mono block heat pump, with its variable speed compressors, ensures perfectly matched heating output and high flow temperatures all year round

DHW cylinder and buffer cylinder with integral hydraulic components including heat pump manager for heat pumps and heating circuit connection in a single casing

Thanks to flow separation, the heating system can be integrated easily and very safely

Optional active cooling by reversing the refrigerant cycle



Set-Components 1



Type	WPL 25 ACS
Product set	WPL Plus Pack 1

Technical data

Energy efficiency class, heat pump W35	A+++
Energy efficiency class, heat pump W55	A++
Energy efficiency class, composite system (heat pump + controller) W35	A+++
Energy efficiency class, composite system (heat pump + controller) W55	A++
Heating output at A7/W35 (EN 14511)	8.00 kW
Heating output at A2/W35 (EN 14511)	8.33 kW
Heating output at A-7/W35 (EN 14511)	12.86 kW
Max. cooling capacity at A35/W7	14.88 kW
Cooling capacity at A35/W18 partial load	6.76 kW
Max. cooling capacity at A35/W18	17.06 kW
COP at A7/W35 (EN 14511)	4.82
COP at A2/W35 (EN 14511)	4.14
COP at A-7/W35 (EN 14511)	2.98
Energy efficiency ratio at A35/W7 max.	2.38
Energy efficiency ratio at A35/W18 partial load	3.76
Energy efficiency ratio at A35/W18 max.	2.83
SCOP 35 °C (EN 14825)	4.53
Sound power level (EN 12102)	55 dB(A)

Min./max. application limits for heat source	-20-40 °C
Max. application limit on the heating side	65 °C
Height	1045 mm
Width	1490 mm
Depth	593 mm
Weight	175 kg
Rated voltage, compressor	230 V
Rated voltage, emergency/auxiliary heater	230 V
Refrigerant	R410A

Set-Components **2**

Type	HSBC 200 S (GB) Set
Product set	WPL Plus Pack 1

Technical data

Energy efficiency class	B
Standby energy consumption/24 h at 65 °C	1.30 kWh
Nominal capacity, DHW cylinder	168 l
Nominal capacity, buffer cylinder	100 l
Surface area, heat exchanger	3.30 m ²
Capacity, heat exchanger	21 l
Height	1908 mm
Width	680 mm
Depth	871 mm
Height when tilted	2107 mm
Weight	203 kg

Set-Components **3**



Type	FET
Product set	WPL Plus Pack 1

Technical data


Width	145 mm
Height	96 mm
Depth	31 mm

Set-Components **4**

Type	ISG web
Product set	WPL Plus Pack 1

Technical data

Version	Wall mounting
10/100 Ethernet	RJ45
CAN	RJ45
RS232	RJ12
Width	158 mm
Height	95 mm
Depth	37 mm
Min./max. application range	0 / 60 °C

Set-Components **5**

Type	FS-WP 28
Product set	WPL Plus Pack 1

Technical data

Connection	G 1 1/4 A / Cu 28 x 1.5
------------	----------------------------

More details regarding set components can be found under the relevant product

Contact information

Do you have additional questions? Then please do not hesitate to contact us, we would be only too happy to help:

Call 0151 436 96

Or send an e-mail to

sales@stiebel-eltron.ie

Only a qualified contractor should carry out the installation, commissioning, maintenance and repair of this appliance. Where applicable and prior to installation the electricity and/or water utility companies should be notified of your intention to install the product.